



Up-to-date Questions and Answers from authentic resources to improve knowledge and pass the exam at very first attempt. ----- Guaranteed.



PCEP-30-02 Dumps
PCEP-30-02 Braindumps
PCEP-30-02 Real Questions
PCEP-30-02 Practice Test
PCEP-30-02 Actual Questions



killexams.com

Python

PCEP-30-02

PCEP - Certified Entry-Level Python Programmer

ORDER FULL VERSION

<https://killexams.com/pass4sure/exam-detail/PCEP-30-02>



Question: 427

What will be the output of the following code snippet: `print(type([]) is list)`?

- A. True
- B. False
- C. None
- D. TypeError

Answer: A

Explanation:

The expression `type([])` returns the type of an empty list, which is `list`. The comparison `is` checks if both operands refer to the same object, and since they do, the output will be `True`.

Question: 428

Which of the following Python statements will correctly create a list containing the numbers 1 to 10 inclusive?

- A. `numbers = [1:10]`
- B. `numbers = list(range(1, 11))`
- C. `numbers = [1, 2, 3, 4, 5, 6, 7, 8, 9, 10]`
- D. `numbers = (1, 10)`

Answer: B

Explanation:

To create a list of numbers from 1 to 10 inclusive, we can use the `range` function with `list()` to convert it into a list.

`numbers = list(range(1, 11))` produces `[1, 2, 3, 4, 5, 6, 7, 8, 9, 10]`.

The other options either use incorrect syntax or create a tuple.

Question: 429

What will be the output of the following code that uses the `filter()` function?

```
nums = [1, 2, 3, 4, 5]
even_nums = list(filter(lambda x: x % 2 == 0, nums))
```

```
print(even_nums)
```

- A. [1, 2, 3]
- B. [2, 4]
- C. [1, 3, 5]
- D. [1, 2, 3, 4, 5]

Answer: B

Explanation: The filter() function applies the lambda function to each element in nums, keeping only even numbers. The resulting list is [2, 4].

Question: 430

What will be the output of the following code?

```
def f(a, b=1, c=2):  
    return a * b + c
```

```
print(f(5, 2))
```

- A. 12
- B. 15
- C. 20
- D. 8
- E. 9
- F. The function will raise an error.

Answer: A

Explanation:

In this function, f takes three parameters, with b and c having default values. When called with 5 for a and 2 for b, it calculates $5 * 2 + 2$, which equals 12.

Question: 431

What will be the output of the following code when executed?

```
def my_function(x):  
    return x + 1
```

```
result = my_function(3)
print(result)
```

- A. 2
- B. 3
- C. 4
- D. None

Answer: C

Explanation:

The function `my_function` takes an argument `x`, adds 1, and returns the result. For the input 3, it returns 4.

Question: 432

Consider the following snippet of code. What will be printed when the function `func` is called with the argument 4?

```
def func(n):
    return (n + 1) if n % 2 == 0 else (n - 1)

print(func(4))
```

- A. 3
- B. 4
- C. 5
- D. 2
- E. None

Answer: C

Explanation:

When `func(4)` is called, since 4 is even ($4 \% 2 == 0$), the function returns $4 + 1$, which equals 5. Therefore, the printed result is 5.

Question: 433

What will be printed by the following code block?

```
def func(a, b):  
    a += b  
    return a  
x = 10  
y = 5  
print(func(x, y))  
print(x)
```

- A. 15, 10
- B. 15, 5
- C. 10, 5
- D. 15, 15

Answer: A

Explanation:

The function func adds b to a and returns the result. It does not modify the original x, so x remains 10.

Question: 434

What is the output of this code?

```
def square_numbers(lst):  
    return [x**2 for x in lst if x > 0]  
print(square_numbers([-1, 0, 1, 2, 3]))
```

- A. [1, 4, 9]
- B. [0, 1, 4, 9]
- C. [1, 2, 3]
- D. [2, 3]
- E. [-1, 0]

Answer: A

Explanation:

The square_numbers function squares only the positive numbers in the input list. For [-1, 0, 1, 2, 3], the positive numbers are 1, 2, and 3, leading to the output [1, 4, 9].

Question: 435

What does the following code output?

```
def check_value(x):  
    return "Positive" if x > 0 else "Negative" if x < 0 else "Zero"  
print(check_value(-10))  
print(check_value(0))  
print(check_value(10))
```

- A. Positive, Negative, Zero
- B. Negative, Zero, Positive
- C. Zero, Negative, Positive
- D. Negative, Positive, Zero

Answer: B

Explanation:

The function checks the value of x and returns "Negative", "Zero", or "Positive" depending on its condition. The outputs correspond correctly to the inputs.

Question: 436

Which of the following statements best describes the purpose of the `__init__` method in a Python class?

- A. It is used to return a string representation of the object.
- B. It initializes the object's attributes when an instance is created.
- C. It is invoked when a class is inherited.
- D. It is used to delete an instance of the object.

Answer: B

Explanation:

The `__init__` method is a special method in Python classes that is automatically called when a new instance of the class is created. It allows you to set the initial state of the object by assigning values to its attributes.

Question: 437

A financial institution is developing a Python program to calculate the compound interest on an investment. The program should account for user inputs and provide the final amount after the specified time. You need to complete the code to meet the requirements.

```
principal = XXX
```

```
rate = YYY
time = ZZZ
amount = principal * (1 + rate / 100) ** time
print('The final amount after {} years is: {:.2f}'.format(time, amount))
```

What should you insert instead of XXX, YYY, and ZZZ?

- A. XXX -> float(input('Enter the principal amount: ')) YYY -> float(input('Enter the interest rate: ')) ZZZ -> int(input('Enter the time in years: '))
- B. XXX -> input('Enter the principal amount: ') YYY -> float(input('Enter the interest rate: ')) ZZZ -> int(input('Enter the time in years: '))
- C. XXX -> float(input('Enter the principal amount: ')) YYY -> input('Enter the interest rate: ') ZZZ -> int(input('Enter the time in years: '))
- D. XXX -> float(input('Enter the principal amount: ')) YYY -> float(input('Enter the interest rate: ')) ZZZ -> input('Enter the time in years: ')

Answer: A

Explanation:

```
principal = float(input('Enter the principal amount: '))
rate = float(input('Enter the interest rate: '))
time = int(input('Enter the time in years: '))
amount = principal * (1 + rate / 100) ** time
print('The final amount after {} years is: {:.2f}'.format(time, amount))
```

The program captures user inputs for principal and rate as floats, and time as an integer. It calculates the compound interest and formats the output to two decimal places.

Question: 438

Which of the following statements about default parameters in Python functions is true?

- A. Default parameters must be specified in every function call.
- B. You cannot use mutable types as default parameters.
- C. Default parameters are evaluated only once at function definition time.

Answer: C

Explanation:

Default parameters in Python are evaluated once when the function is defined, not each time the function is called.

Question: 439

What will be the output of the following code snippet involving a class method and class variable?

```
class Counter:
    count = 0
    def increment(self):
        Counter.count += 1
counter1 = Counter()
counter1.increment()
counter2 = Counter()
counter2.increment()
print(Counter.count)
```

- A. 1
- B. 2
- C. 0
- D. Error

Answer: B

Explanation:

The class variable `count` is shared among all instances of the `Counter` class. Each time `increment()` is called, `count` increases by 1. After two calls, the count is 2.

Question: 440

Examine the following code snippet and identify which statements regarding the use of `*args` and `**kwargs` in function definitions are true: (Select All That Apply)

```
def function_with_args(*args, **kwargs):
    print(args)
    print(kwargs)
```

```
function_with_args(1, 2, three='3', four='4')
```

- A. The output will be (1, 2) and {'three': '3', 'four': '4'}
- B. `*args` allows for variable numbers of positional arguments
- C. `**kwargs` allows for variable numbers of keyword arguments
- D. Both `*args` and `**kwargs` can be used in the same function

Answer: A, B, C, D

Explanation:

The `*args` parameter collects extra positional arguments into a tuple, while `**kwargs` collects additional keyword arguments into a dictionary. The output confirms that `args` contains (1, 2) and `kwargs` contains

{'three': '3', 'four': '4'}. Both can be used together in the same function definition.

Question: 441

What will be the output of the following code snippet?

```
def func(x):  
    return x * 2  
  
print(func(func(3)))
```

- A. 6
- B. 3
- C. 12
- D. 9

Answer: C

Explanation:

The function func takes an argument x and returns $x * 2$.

When func(3) is called, it returns 6.

Then, func(6) is called, which returns 12.

Thus, the final output is 12.

Question: 442

How do you define a function that can take an arbitrary number of positional arguments and keyword arguments?

- A. `def my_function(*args, kwargs):`
- B. `def my_function(args, kwargs):`
- C. `def my_function(*args, **kwargs):`

Answer: A

Explanation:

The syntax `*args` captures positional arguments as a tuple, while `**kwargs` captures keyword arguments as a dictionary.

Question: 443

A healthcare application requires a Python program to calculate the Body Mass Index (BMI) from a user's weight and height. The program must handle exceptions for invalid input and provide a clear output. You need to complete the code to meet the requirements.

```
weight = XXX
height = YYY
try:
    bmi = weight / (height ** 2)
except ZeroDivisionError:
    print('Height cannot be zero.')
else:
    print('Your BMI is: {:.2f}'.format(bmi))
```

What should you insert instead of XXX and YYY?

- A. XXX -> float(input('Enter your weight in kg: ')) YYY -> float(input('Enter your height in meters: '))
- B. XXX -> input('Enter your weight in kg: ') YYY -> input('Enter your height in meters: ')
- C. XXX -> float(input('Enter your weight in kg: ')) YYY -> input('Enter your height in meters: ')
- D. XXX -> input('Enter your weight in kg: ') YYY -> float(input('Enter your height in meters: '))

Answer: A

Explanation:

```
weight = float(input('Enter your weight in kg: '))
height = float(input('Enter your height in meters: '))
try:
    bmi = weight / (height ** 2)
except ZeroDivisionError:
    print('Height cannot be zero.')
else:
    print('Your BMI is: {:.2f}'.format(bmi))
```

The program captures user input as a float for weight and height.

It handles division by zero, which can occur if height is zero, and formats the BMI output to two decimal places.

Question: 444

Which of the following statements correctly illustrates the concept of variable scope in Python?

- A. Variables defined inside a function can be accessed from outside the function.
- B. Global variables can be modified inside a function using the global keyword.
- C. Local variables can be accessed from any part of the program.
- D. The scope of a variable is determined by the order of its declaration.

Answer: B

Explanation:

In Python, variables defined inside a function are local to that function and cannot be accessed from outside. To modify a global variable inside a function, you must declare it using the global keyword.

Question: 445

What will be printed by the following code snippet when executed?

```
def func(x):  
    if x >= 0:  
        return x  
    else:  
        return func(-x)  
  
print(func(-5))
```

- A. 5
- B. -5
- C. 0

Answer: A

Explanation:

The function func checks if x is non-negative.

When func(-5) is called, -5 is negative, so it calls func(5).
Now, func(5) checks and finds that 5 is non-negative and returns 5.
Thus, the output will be 5.

Question: 446

When using keyword arguments in a function, which of the following is a valid way to call the function?

- A. my_function(x=1, 2)
- B. my_function(2, x=1)
- C. my_function(2, y=3)

Answer: B

Explanation:

Keyword arguments can be specified in any order. However, positional arguments must appear before keyword arguments.

Question: 447

What does the following code output?

```
def is_palindrome(s):  
    return s == s[::-1]  
print(is_palindrome("racecar"))
```

- A. True
- B. False
- C. racecar
- D. 1
- E. 0

Answer: A

Explanation:

The function `is_palindrome` checks if the string `s` is the same forwards and backwards. "racecar" is a palindrome, so the output is `True`.

Question: 448

Consider the following code snippet. What will be the output when this code is executed?

```
def merge_dicts(dict1, dict2):  
    return {**dict1, **dict2}
```

```
dict_a = {'a': 1, 'b': 2}  
dict_b = {'b': 3, 'c': 4}  
print(merge_dicts(dict_a, dict_b))
```

- A. {'a': 1, 'b': 2, 'c': 4}
- B. {'a': 1, 'b': 3, 'c': 4}
- C. {'a': 1, 'b': 2}
- D. {'b': 3, 'c': 4}

Answer: B

Explanation:

The function `merge_dicts` combines two dictionaries. If there are overlapping keys, the values from the second dictionary (`dict2`) take precedence. Hence, the resulting dictionary is `{'a': 1, 'b': 3, 'c': 4}`.





KILLEXAMS.COM

Killexams.com is an online platform that offers a wide range of services related to certification exam preparation. The platform provides actual questions, exam dumps, and practice tests to help individuals prepare for various certification exams with confidence. Here are some key features and services offered by Killexams.com:



Actual Exam Questions: Killexams.com provides actual exam questions that are experienced in test centers. These questions are updated regularly to ensure they are up-to-date and relevant to the latest exam syllabus. By studying these actual questions, candidates can familiarize themselves with the content and format of the real exam.

Exam Dumps: Killexams.com offers exam dumps in PDF format. These dumps contain a comprehensive collection of questions and answers that cover the exam topics. By using these dumps, candidates can enhance their knowledge and improve their chances of success in the certification exam.

Practice Tests: Killexams.com provides practice tests through their desktop VCE exam simulator and online test engine. These practice tests simulate the real exam environment and help candidates assess their readiness for the actual exam. The practice tests cover a wide range of questions and enable candidates to identify their strengths and weaknesses.

Guaranteed Success: Killexams.com offers a success guarantee with their exam dumps. They claim that by using their materials, candidates will pass their exams on the first attempt or they will refund the purchase price. This guarantee provides assurance and confidence to individuals preparing for certification exams.

Updated Content: Killexams.com regularly updates its question bank and exam dumps to ensure that they are current and reflect the latest changes in the exam syllabus. This helps candidates stay up-to-date with the exam content and increases their chances of success.

Technical Support: Killexams.com provides free 24x7 technical support to assist candidates with any queries or issues they may encounter while using their services. Their certified experts are available to provide guidance and help candidates throughout their exam preparation journey.